

DS-2CD1643G2-IZ(2.8-12mm) - Hikvision PoE-IP-Bullet-Kamera für Außenbereiche mit Nachtsicht mit PoE

Brand HIKVISION Range Value Image sensor 1/3" Progressive Scan CMOS Maximum resolution 4 Megapixel (2560x1440)
Main Stream rate 20 fps (2560x1440), 25 fps (1920x1080, 1280x720) Extra Stream rate 25 fps (1280x720, 640x480,
640x360) Compression H.265+ / H.264+ / H.265 / H.264 Bitrate 32 Kbps ~ 8 Mbps Lens Motorized varifocal 2.8~12 mm
Viewing Angle (FOV) H: 95.9~29.2°, V: 50.6~16.4°, D: 114.7~33.5° Electronic Shutter 1/3~1/100.000 s Minimum illumination
Colour: 0.005 Lux @(F1.6, AGC ON)
0 Lux with EXIR IR range 50 m Day/Night Removable mechanical ICR filter Image improvements WDR (120 dB), BLC, HLC,
3D-DNR, AGC, AWB, ROI, Mirror function, Privacy masking Motion Detection Motion detection 2.0 with human and vehicle
classification applied in motion detection. Internal memory MicroSD card slot up to 256 GB Network interface Ethernet 10 /
100 BaseT Remote access Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Interoperability ONVIF, ISAPI Power DC 12 V / 900 mA / 11 W max. / IEEE802.3af PoE Degree of protection Weatherproof
IP67 Temp. operation -30° C ~ +60° C Dimensions Ø 105 mm x 244.4 mm (D) Base dimensions Ø base 105 mm / Ø entre
tornillos 89 mm / 4 tornillos Weight 745 g