XS-IPDM844ZAWH-8

X-Security IP Dome Camera

1/1.8” 8 Megapixel Progressive CMOS

3840 x 2160 4K

Compression H.265+

3.7~11 mm Motorised Varifocal

Autofocus Lens

Audio / Alarms / WDR (120dB) / ICR

X-Security
IP dome camera
1/1.8" Progressive CMOS
8 Megapixel (3840x2160)
0 Lux
IR 30m
3.7~11 mm motorised varifocal autofocus lens
Compression H.265+/H.265/H.264+/H.264
Dual stream - RJ-45 10/100 BaseT
PoE IEEE802.3af - WDR120dB
Weatherproof IP67 IK10
IR Cut
Audio
Alarm
SD storage
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible

Specifications

Brand	X-SECURITY
Image sensor	1/1.8" Progressive CMOS
Resolution	4K(3840×2160)/6M(3072×2048)/5M(2560×1920)/ 3M(2048x1536)/3M(2304×1296)/ 1080P(1920×1080)/1.3M(1280x960)/ 720P(1280×720)/D1(704×576/704×480) / VGA(640×480)/CIF(352×288/352×240)
Maximum resolution	8 Megapixel (3840x2160)
Main Stream rate	4K (1~25 FPS)
Extra Stream rate	D1(1 ~ 25fps)
Compression	H.265+/H.265/H.264+/H.264
Lens	3.7 ~ 11 mm Motorised Varifocal (H: 111º ~ 55º)
Minimum illumination	0.004 Lux (Colour)
Infrared lighting	0 Lux / IR LEDs (30 m)
Image improvements	WDR, BLC, HLC, AWB, AGC, 3D-NR, Smart IR, Motion detection, ROI, Flip/Mirror, Privacy Mask
Day / Night	Auto ICR
Network interface	Ethernet 10/100 BaseT
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF
Storage	SD card up to 128GB
Audio	1 input / 1 output
Alarms	1 input / 1 output
Power supply	DC 12 V / 510 mA, PoE IEEE802.3af
Temp. operation	-30º C ~ 60º C
Degree of protection	Weatherproof IP67, Anti-vandal IK10
Dimensions	89 mm (D) x 122 (Ø) mm
Weight	490 g