# XS-IPDM844ZWA-4

4 MP IP Camera

1/3” Progressive Scan CMOS

Compression H.265+ / H.265 / H.264+ / H.264

Motorised Lens with Autofocus 2.7~12mm

IR LEDs Range 30 m | Audio | Alarms

WEB, DSS/PSS, Smartphone and NVR

X-Security
IP camera
1/3” Progressive CMOS
4 Megapixel (2688x1520)
2.7~13.5 mm motorised varifocal autofocus lens
0 Lux - IR Array Range 30 m
Compression H.265+/H.265/H.264+/H.264
RJ-45 10/100 BaseT
PoE IEEE802.3af
Weatherproof IP67
Audio
IR Cut
WDR
SD card recording
WEB Interface, CMS (DSS/ PSS), Smartphone and NVR
ONVIF Compatible

# Specifications

| | |
|---|---|
| **Brand** | X-Security |
| **Image sensor** | 1/3" Progressive CMOS |
| **Maximum resolution** | 4 Megapixel (2688x1520) |
| **Main Stream rate** | 4Mp (1 ~ 25fps) |
| **Extra Stream rate** | D1 / 720 p(1 ~ 25 FPS) |
| **Compression** | H.265+/H.265/H.264+/H.264 |
| **Bitrate** | 32 Kbps ~ 10 Mbps |
| **Lens** | Motorised vari-focal Autofocus Auto-iris 2.7~ 13.5mm (H: 104º ~ 28º) |
| **Minimum illumination** | 0.03 Lux / F1.4 (Colour) |
| **Infrared lighting** | 0 Lux / IR LEDs Array (30 m) |
| **Image improvements** | WDR, Smart IR, BLC, HLC, AWB, AGC, 3D-NR, Privacy Masking, Motion Detection, ROI |
| **Day / Night** | Removable mechanical ICR filter |
| **Network interface** | Ethernet 10/100 BaseT |
| **Internal memory** | Slot for MicroSD card, Max 128 GB |
| **Alarms** | 1 Input / 1 Relay |
| **Audio** | 1 Input / 1 Output |
| **Remote access** | Web browser, CMS Software (DSS/PSS), Smartphone (DMSS) and NVR |
| **Interoperability** | ONVIF |
| **Power supply** | DC 12 V / 710 mA, PoE IEEE802.3af |
| **Degree of protection** | Weatherproof IP67, Anti-vandal IK10 |
| **Temp. operation** | -30º C ~ +60º C |
| **Dimensions** | 90 mm (D) x 122 (Ø) mm |
| **Weight** | 500g |