XS-IPPTZ0125ISTWH-2

X-Security IP PTZ Auto-Tracking Positioning System

1/2.8” Sony© 2 Megapixel Starvis

Compression

H.265+/H.265/H.264+/H.264

4.8 ~ 120 mm (25X) Varifocal Lens

WDR | PoE+ | IVS

Audio | Alarms | SmartDetection

X-Security
PT Auto-Tracking IP Camera
Average speed 120º/segundo
25X Optical zoom
1/2.8" Sony© Starvis CMOS Starlight
2 Megapixel (1920x1080)
4.8~120 mm Varifocal lens
IR Range 150 m
Compression H.265+/H-265/H.264+/H.264
RJ-45 10/100 BaseT
PoE+ 802.3at
Weatherproof IP67
Audio
IR Cut
WDR
Alarms
Smart function: supports Auto-Tracking and IVS
WEB, CMS (DSS/PSS), Smartphone and NVR interface
ONVIF Compatible
Junction box included

Specifications

Brand	X-Security
Image sensor	1/2.8" Sony© Starvis CMOS Starlight
Resolution	1080P(1920x1080) / 1.3M(1280x960) / 720P(1280x720) / D1(704x576/704x480) / CIF(352x288/352x240)
Compression	H.265+/H.265/H.264+/H.264 (video), G.711a/G.711Mu/AAC/G.722 / G.726/G.729/ MPEG2-L2 (audio)
Main Stream rate	1080P/1.3M/720P(1~50/60fps)
Extra Stream rate	2º: D1/CIF(1 ~ 25/30fps), 3º: 1080P/1.3M/720P/D1/CIF (1~25/30fps)
Bitrate	448 Kbps ~ 8 Mbps
Lens	4.8~120mm Vari-focal (25X) Optical zoom, Auto Iris, Auto Focus
Digital zoom	16 X
Image improvements	WDR (120dB), 2D/ 3DNR, HLC, BLC, ATW, AGC, MD, ROI, EIS, Privacy Mask
Minimum illumination	0.005 Lux (colour) / 0 Lux (B/N) IR LEDs (150m)
Day / Night	Removable mechanical ICR filter
Network interface	Ethernet 10/100 BaseT/TX
Remote access	WEB interface, CMS software, mobile application and NVR
Memory	Slot for Micro SD card (Max 128 GB)
Pan/Tilt Range	Horizontal: 0°~360°, Vertical: -90°~90° auto flip 180°
Manual speed	Horizontal: 0.1°~120° /s, Vertical: 0.1°~75° /s
Speed between Presets	Horizontal: 120° /s, Vertical: 75° /s
Preset positions	300, 5 auto pattern, 8 tour, auto pan, auto scan
Communication	DH-SD
Alarms	2 inputs / 1 relay NO/NC
Audio	1 input (Line In) / 1 output (Line Out)
Power supply	12VDC / 4 A, PoE+ (802.3at)
Degree of protection	Weatherproof IP67, Vandal-proof IK10
Temp. operation	-40º C ~ 70º C
Dimensions	291 mm (H) x 161 (W) x 153.4 (D) mm
Weight	3600 g